



商品名

A6063BE-T6

JIS規格アルミニウム及びアルミニウム合金棒

JIS-H 4040

| 外径(mm) | 長さ(mm) | 引張強さ N/mm ² | 耐力 N/mm ² | 伸び % |
|--------|--------|---------------------------|-------------------------|---------|
| 40 | 4000 | | | |
| 45 | 4000 | | | |
| 50 | 4000 | | | |
| 55 | 4000 | | | |
| 60 | 4000 | | | |
| 70 | 4000 | | | |
| 75 | 4000 | | | |
| 80 | 4000 | | | |
| 85 | 4000 | | | |
| 90 | 4000 | | | |
| 95 | 4000 | | | |
| 100 | 4000 | | | |
| 110 | 4000 | | | |
| 120 | 4000 | | | |
| 130 | 4000 | | | |
| 140 | 4000 | | | |
| 150 | 4000 | | | |
| 160 | 4000 | | | |
| 180 | 4000 | | | |
| 200 | 4000 | | | |
| 210 | 4000 | | | |
| 230 | 4000 | | | |
| 250 | 4000 | | | |
| 300 | 2000 | | | |
| 310 | 2000 | | | |
| 330 | 2000 | | | |
| 350 | 2000 | | | |
| 360 | 2000 | | | |